

HIGH PERFORMANCE
END MILLS

Series X5, G5

NEW
SERIES

SERIES HIGHLIGHT

S M P K

High Performance End Mills

X5 BALIQ® ALCRONOS Coating (AlCrN)


G5 BALIQ® TISINOS PRO Coating (AlTiSiN)

X5 Target Materials:

Stainless Steel (Inox, Austenitic/Martensitic)
Carbon Tools Steels (Up to 50 HRC)
Cast Iron


G5 Target Materials:

Heat Resistant Super Alloys
PH Stainless Steels (Inox, 13-8, 15-5, 17-4, Martensitic)
Conditioned Tool Steels (50-70 HRC)




X5

G5



CALCULATE IDEAL PARAMETERS
FOR THE X5 AND G5 IN YOUR
APPLICATION WITH THE GARR
TECHNICAL ADVISOR



← View the X5

View the G5 →



TOLERANCES

<i>d1</i>	+0.000" -0.002" (+0.000mm -0.050mm)
<i>d2</i>	h6
<i>r</i>	+0.001" -0.001" (+0.025 -0.025mm)

THE NEXT GENERATION

Series X5, G5



TECH
PAGES
302-303

.1562" - .2188"
(3.967mm - 5.558mm)

X5 Recommended for Low, Medium, and High Carbon Tool Steels (up to 50 HRC), cast iron, and stainless steel (Inox).

G5 Recommended for tough machining materials such as Heat Resistant Super Alloys, PH Stainless steels (Inox), and conditioned tool steels. (50-70 HRC)

5 Flute High Performance End Mills

X5 BALIQ® ALCRONOS Coating (AlCrN-based)

G5 BALIQ® TISINOS PRO Coating (AlTiSiN)

Solid submicron grain carbide - center cutting

h6 shank tolerance


Engineered for High Efficiency Milling

Variable flute grind

Honed edge treatment

Polished fluting

Material and condition specific coatings



X5 EDP#	G5 EDP#	<i>d1</i> † Diameter		<i>d2</i> Shank Diameter	<i>l1</i> Overall Length	<i>l2</i> Flute Length	<i>r</i> Corner Radius	LIST PRICE	
		Decimal	Metric						
31400	34700	.1562	5/32"	3.967	1/4"	2"	5/16"	-	30.15
31401	34701	.1562	5/32"	3.967	1/4"	2"	5/16"	.010"	34.04
31402	34702	.1562	5/32"	3.967	1/4"	2"	7/16"	-	30.15
31403	34703	.1562	5/32"	3.967	1/4"	2"	7/16"	.010"	34.04
31404	34704	.1562	5/32"	3.967	1/4"	2-1/2"	9/16"	-	31.90
31405	34705	.1562	5/32"	3.967	1/4"	2-1/2"	9/16"	.010"	35.58
31406	34706	.1575		4.000	6.0	50	8	-	31.17
31407	34707	.1575		4.000	6.0	50	8	0.30	35.16
31408	34708	.1575		4.000	6.0	50	8	0.50	35.16
31409	34709	.1575		4.000	6.0	50	16	-	31.17
31410	34710	.1575		4.000	6.0	50	16	0.30	35.16
31411	34711	.1575		4.000	6.0	50	16	0.50	35.16
31412	34712	.1875	3/16"	4.763	1/4"	2"	5/16"	-	29.83
31413	34713	.1875	3/16"	4.763	1/4"	2"	5/16"	.010"	33.68
31414	34714	.1875	3/16"	4.763	1/4"	2"	5/16"	.015"	33.68
31415	34715	.1875	3/16"	4.763	1/4"	2"	7/16"	-	29.83
31416	34716	.1875	3/16"	4.763	1/4"	2"	7/16"	.010"	33.68
31417	34717	.1875	3/16"	4.763	1/4"	2"	7/16"	.015"	33.68
31418	34718	.1875	3/16"	4.763	1/4"	2-1/2"	9/16"	-	31.58
31419	34719	.1875	3/16"	4.763	1/4"	2-1/2"	9/16"	.010"	35.21
31420	34720	.1875	3/16"	4.763	1/4"	2-1/2"	9/16"	.015"	35.21
31421	34721	.1969		5.000	6.0	50	10	-	30.53
31422	34722	.1969		5.000	6.0	50	10	0.30	34.43
31423	34723	.1969		5.000	6.0	50	10	0.50	34.43
31424	34724	.1969		5.000	6.0	65	15	-	32.22
31425	34725	.1969		5.000	6.0	65	15	0.30	36.07
31426	34726	.1969		5.000	6.0	65	15	0.50	36.07
31427	34727	.2188	7/32"	5.558	1/4"	2"	3/8"	-	29.53
31428	34728	.2188	7/32"	5.558	1/4"	2"	3/8"	.015"	33.34
31429	34729	.2188	7/32"	5.558	1/4"	2-1/2"	3/4"	-	31.25
31430	34730	.2188	7/32"	5.558	1/4"	2-1/2"	3/4"	.015"	34.85

HIGH PERFORMANCE
END MILLS

70 ← G5
X5
35 ←
MATERIAL HARDNESS (Rc)
0 ←

continued →

Series X5, G5 (continued)

.2362" - .3750"
(6.000mm - 9.525mm)

HIGH PERFORMANCE
END MILLS

X5 EDP#	G5 EDP#	$d1$ † Diameter		$d2$ Shank Diameter	$l1$ Overall Length	$l2$ Flute Length	r Corner Radius	LIST PRICE	
		Decimal	Metric						
31431	34731	.2362	6.000	6	50	13	-	29.62	
31432	34732	.2362	6.000	6	50	13	0.30	33.40	
31433	34733	.2362	6.000	6	50	13	0.50	33.40	
31434	34734	.2362	6.000	6	65	19	-	31.25	
31435	34735	.2362	6.000	6	65	19	0.30	34.99	
31436	34736	.2362	6.000	6	65	19	0.50	34.99	
31437	34737	.2362	6.000	6	75	26	-	44.57	
31438	34738	.2362	6.000	6	75	26	0.30	50.07	
31439	34739	.2362	6.000	6	75	26	0.50	50.07	
31440	34740	.2500	1/4"	6.350	1/4"	2-1/2"	1/2"	-	30.31
31441	34741	.2500	1/4"	6.350	1/4"	2-1/2"	1/2"	.015"	33.80
31442	34742	.2500	1/4"	6.350	1/4"	2-1/2"	1/2"	.030"	33.80
31443	34743	.2500	1/4"	6.350	1/4"	2-1/2"	3/4"	-	30.31
31444	34744	.2500	1/4"	6.350	1/4"	2-1/2"	3/4"	.010"	33.80
31445	34745	.2500	1/4"	6.350	1/4"	2-1/2"	3/4"	.015"	33.80
31446	34746	.2500	1/4"	6.350	1/4"	2-1/2"	3/4"	.020"	33.80
31447	34747	.2500	1/4"	6.350	1/4"	2-1/2"	3/4"	.030"	33.80
31448	34748	.2500	1/4"	6.350	1/4"	2-1/2"	3/4"	.060"	33.80
31449	34749	.2500	1/4"	6.350	1/4"	3"	1"	-	44.16
31450	34750	.2500	1/4"	6.350	1/4"	3"	1"	.015"	48.15
31451	34751	.2500	1/4"	6.350	1/4"	3"	1"	.030"	48.15
31452	34752	.3125	5/16"	7.938	5/16"	2-1/2"	13/16"	-	38.19
31453	34753	.3125	5/16"	7.938	5/16"	2-1/2"	13/16"	.015"	41.05
31454	34754	.3125	5/16"	7.938	5/16"	2-1/2"	13/16"	.020"	41.05
31455	34755	.3125	5/16"	7.938	5/16"	2-1/2"	13/16"	.030"	41.05
31456	34756	.3150		8.000	8	65	22	-	39.45
31457	34757	.3150		8.000	8	65	22	0.50	42.58
31458	34758	.3150		8.000	8	65	22	1.00	42.58
31459	34759	.3150		8.000	8	75	32	-	54.95
31460	34760	.3150		8.000	8	75	32	0.50	59.36
31461	34761	.3150		8.000	8	75	32	1.00	59.36
31462	34762	.3750	3/8"	9.525	3/8"	2"	1/2"	-	40.81
31463	34763	.3750	3/8"	9.525	3/8"	2"	1/2"	.015"	46.29
31464	34764	.3750	3/8"	9.525	3/8"	2"	1/2"	.020"	46.29
31465	34765	.3750	3/8"	9.525	3/8"	2"	1/2"	.030"	46.29
31466	34766	.3750	3/8"	9.525	3/8"	2"	5/8"	-	40.81
31467	34767	.3750	3/8"	9.525	3/8"	2"	5/8"	.015"	46.29
31468	34768	.3750	3/8"	9.525	3/8"	2"	5/8"	.020"	46.29
31469	34769	.3750	3/8"	9.525	3/8"	2"	5/8"	.030"	46.29
31595	34886	.3750	3/8"	9.525	3/8"	2-1/2"	5/8"	.060"	47.84
31470	34770	.3750	3/8"	9.525	3/8"	2-1/2"	7/8"	-	44.92
31471	34771	.3750	3/8"	9.525	3/8"	2-1/2"	7/8"	.015"	47.84
31472	34772	.3750	3/8"	9.525	3/8"	2-1/2"	7/8"	.020"	47.84
31473	34773	.3750	3/8"	9.525	3/8"	2-1/2"	7/8"	.030"	47.84
31588	34879	.3750	3/8"	9.525	3/8"	2-1/2"	1"	-	44.92
31589	34880	.3750	3/8"	9.525	3/8"	2-1/2"	1"	.010"	47.84
31590	34881	.3750	3/8"	9.525	3/8"	2-1/2"	1"	.015"	47.84
31591	34882	.3750	3/8"	9.525	3/8"	2-1/2"	1"	.020"	47.84
31592	34883	.3750	3/8"	9.525	3/8"	2-1/2"	1"	.030"	47.84
31593	34884	.3750	3/8"	9.525	3/8"	2-1/2"	1"	.060"	47.84
31474	34774	.3750	3/8"	9.525	3/8"	3"	1"	-	58.61
31475	34775	.3750	3/8"	9.525	3/8"	3"	1"	.015"	62.69
31476	34776	.3750	3/8"	9.525	3/8"	3"	1"	.020"	62.69
31477	34777	.3750	3/8"	9.525	3/8"	3"	1"	.030"	62.69
31594	34885	.3750	3/8"	9.525	3/8"	3"	1"	.060"	62.69
31478	34778	.3750	3/8"	9.525	3/8"	3"	1-1/4"	-	58.61
31479	34779	.3750	3/8"	9.525	3/8"	3"	1-1/4"	.015"	62.69

G5
 X5
 MATERIAL HARDNESS (Rc)
 70
 35
 0

X5 EDP#	G5 EDP#	$d1^{\dagger}$ Diameter		$d2$ Shank Diameter	$l1$ Overall Length	$l2$ Flute Length	r Corner Radius	LIST PRICE
		Decimal	Metric					
31480	34780	.3937	10.000	10	70	26	-	57.49
31481	34781	.3937	10.000	10	70	26	0.50	61.37
31482	34782	.3937	10.000	10	70	26	1.00	61.37
31483	34783	.3937	10.000	10	75	32	-	67.35
31484	34784	.3937	10.000	10	75	32	0.50	72.04
31485	34785	.3937	10.000	10	75	32	1.00	72.04
31486	34786	.4724	12.000	12	65	19	-	69.01
31487	34787	.4724	12.000	12	65	19	0.30	79.54
31488	34788	.4724	12.000	12	65	19	0.50	79.54
31489	34789	.4724	12.000	12	65	19	1.00	79.54
31490	34790	.4724	12.000	12	75	26	-	73.35
31491	34791	.4724	12.000	12	75	26	0.30	88.22
31492	34792	.4724	12.000	12	75	26	0.50	88.22
31493	34793	.4724	12.000	12	75	26	1.00	88.22
31494	34794	.4724	12.000	12	75	32	-	73.35
31495	34795	.4724	12.000	12	75	32	0.30	88.22
31496	34796	.4724	12.000	12	75	32	0.50	88.22
31497	34797	.4724	12.000	12	75	32	1.00	88.22
31498	34798	.4724	12.000	12	100	42	-	95.91
31499	34799	.4724	12.000	12	100	42	0.30	101.34
31500	34800	.4724	12.000	12	100	42	0.50	101.34
31501	34801	.4724	12.000	12	100	42	1.00	101.34
31502	34802	.4724	12.000	12	100	50	-	95.91
31503	34803	.4724	12.000	12	100	50	0.30	101.34
31504	34804	.4724	12.000	12	100	50	0.50	101.34
31505	34805	.4724	12.000	12	100	50	1.00	101.34
31506	34806	.5000	12.700	1/2"	2-1/2"	5/8"	-	66.37
31507	34807	.5000	12.700	1/2"	2-1/2"	5/8"	.010"	76.45
31508	34808	.5000	12.700	1/2"	2-1/2"	5/8"	.015"	76.45
31509	34809	.5000	12.700	1/2"	2-1/2"	5/8"	.020"	76.45
31511	34810	.5000	12.700	1/2"	2-1/2"	5/8"	.030"	76.45
31596	34887	.5000	12.700	1/2"	2-1/2"	5/8"	.125"	76.45
31512	34811	.5000	12.700	1/2"	3"	1"	-	70.60
31513	34812	.5000	12.700	1/2"	3"	1"	.015"	84.80
31514	34813	.5000	12.700	1/2"	3"	1"	.030"	84.80
31515	34814	.5000	12.700	1/2"	3"	1"	.060"	84.80
31516	34815	.5000	12.700	1/2"	3"	1-1/4"	-	70.60
31517	34816	.5000	12.700	1/2"	3"	1-1/4"	.010"	84.80
31518	34817	.5000	12.700	1/2"	3"	1-1/4"	.015"	84.80
31519	34818	.5000	12.700	1/2"	3"	1-1/4"	.020"	84.80
31521	34819	.5000	12.700	1/2"	3"	1-1/4"	.030"	84.80
31522	34820	.5000	12.700	1/2"	3"	1-1/4"	.060"	84.80
31523	34821	.5000	12.700	1/2"	3"	1-1/4"	.125"	84.80
31524	34822	.5000	12.700	1/2"	4"	1-5/8"	-	93.35
31525	34823	.5000	12.700	1/2"	4"	1-5/8"	.015"	98.82
31526	34824	.5000	12.700	1/2"	4"	1-5/8"	.020"	98.82
31527	34825	.5000	12.700	1/2"	4"	1-5/8"	.030"	98.82
31528	34826	.5000	12.700	1/2"	4"	2-1/8"	-	93.35
31529	34827	.5000	12.700	1/2"	4"	2-1/8"	.015"	98.82
31530	34828	.5000	12.700	1/2"	4"	2-1/8"	.030"	98.82
31531	34829	.6250	15.875	5/8"	3"	1"	-	118.16
31532	34830	.6250	15.875	5/8"	3"	1"	.015"	123.75
31533	34831	.6250	15.875	5/8"	3"	1"	.030"	123.75
31534	34832	.6250	15.875	5/8"	3-1/2"	1-1/2"	-	121.91
31535	34833	.6250	15.875	5/8"	3-1/2"	1-1/2"	.015"	127.52
31536	34834	.6250	15.875	5/8"	3-1/2"	1-1/2"	.030"	127.52
31537	34835	.6250	15.875	5/8"	3-1/2"	1-1/2"	.060"	127.52

70 → G5
X5
35 → MATERIAL HARDNESS (Rc)
0 →


continued →

Series X5, G5 (continued)

.6250" - 1.000"
(15.875mm - 25.400mm)

X5 EDP#	G5 EDP#	$d1$ † Diameter		$d2$ Shank Diameter	$l1$ Overall Length	$l2$ Flute Length	r Corner Radius	LIST PRICE	
		Decimal	Metric						
31538	34836	.6250	5/8"	15.875	5/8"	4"	1-3/4"	-	129.79
31539	34837	.6250	5/8"	15.875	5/8"	4"	1-3/4"	.015"	138.06
31541	34838	.6250	5/8"	15.875	5/8"	4"	1-3/4"	.030"	138.06
31542	34839	.6250	5/8"	15.875	5/8"	4"	2-1/8"	-	129.79
31543	34840	.6250	5/8"	15.875	5/8"	4"	2-1/8"	.015"	138.06
31544	34841	.6250	5/8"	15.875	5/8"	4"	2-1/8"	.030"	138.06
31545	34842	.6299		16.000	16	88	32	-	126.91
31546	34843	.6299		16.000	16	88	32	0.50	132.77
31548	34844	.6299		16.000	16	88	32	1.00	132.77
31549	34845	.6299		16.000	16	100	40	-	135.01
31550	34846	.6299		16.000	16	100	40	0.50	140.80
31551	34847	.6299		16.000	16	100	40	1.00	140.80
31552	34848	.6299		16.000	16	100	50	-	135.01
31553	34849	.6299		16.000	16	100	50	0.50	140.80
31554	34850	.6299		16.000	16	100	50	1.00	140.80
31555	34851	.7500	3/4"	19.050	3/4"	4"	1-5/8"	-	166.27
31556	34852	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.015"	174.62
31558	34853	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.030"	174.62
31559	34854	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.060"	174.62
31561	34855	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.090"	174.62
31562	34856	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.125"	174.62
31563	34857	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.190"	174.62
31564	34858	.7500	3/4"	19.050	3/4"	4"	1-5/8"	.250"	174.62
31565	34859	.7500	3/4"	19.050	3/4"	5"	2-1/4"	-	223.52
31566	34860	.7500	3/4"	19.050	3/4"	5"	2-1/4"	.030"	242.13
31567	34861	.7500	3/4"	19.050	3/4"	5"	2-1/4"	.060"	242.13
31568	34862	.7500	3/4"	19.050	3/4"	5"	2-1/4"	.125"	242.13
31569	34863	.7500	3/4"	19.050	3/4"	6"	3-1/4"	-	266.17
31571	34864	.7500	3/4"	19.050	3/4"	6"	3-1/4"	.030"	292.00
31572	34865	.7500	3/4"	19.050	3/4"	6"	3-1/4"	.060"	292.00
31573	34866	.7500	3/4"	19.050	3/4"	6"	3-1/4"	.125"	292.00
31574	34867	.7874		20.000	20	100	38	-	228.54
31575	34868	.7874		20.000	20	100	38	0.50	250.42
31576	34869	.7874		20.000	20	100	38	1.00	250.42
31578	34870	.7874		20.000	20	100	50	-	228.54
31579	34871	.7874		20.000	20	100	50	0.50	250.42
31581	34872	.7874		20.000	20	100	50	1.00	250.42
31582	34873	1.000	1"	25.400	1"	4"	1-1/2"	-	250.93
31583	34874	1.000	1"	25.400	1"	4"	1-1/2"	.030"	298.62
31584	34875	1.000	1"	25.400	1"	4"	1-1/2"	.060"	298.62
31585	34876	1.000	1"	25.400	1"	4"	1-1/2"	.125"	298.62
31586	34877	1.000	1"	25.400	1"	5"	2-1/2"	-	313.08
31587	34878	1.000	1"	25.400	1"	5"	2-1/2"	.030"	370.75

G5 ← 70
 X5
 ← 35
 MATERIAL HARDNESS (Rc)
 0



QUICKLY CALCULATE IDEAL PARAMETERS FOR THE X5 OR G5
IN YOUR APPLICATION WITH OUR ONLINE CALCULATOR.

NO REGISTRATION REQUIRED.

CHECK OUT THE
GARR TECHNICAL ADVISOR

