


GARR TOOL Milling Guide for TMS / TMR (HIGH EFFICIENCY MILLING)

NOTE - CHIP THINNING CALCULATION ALREADY APPLIED

CHIPLOAD PER TOOTH (Fz) AT 2% RADIAL ENGAGEMENT (USING PROGRAMMED CALCULATION - SEE PAGE 304)

SPINDLE INTERFACE MUST BE SCRUTINIZED WHEN USING 5/8" DIAMETER AND LARGER END MILLS

ISO Material	SFM (Vc)	CHIPLOAD PER TOOTH (Fz)							
		1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	
S	TITANIUM ALLOYS								
	6Al-4V	250 - 400	.0020" - .0042"	.0030" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"
	5553	150 - 250	.0015" - .0028"	.0018" - .0035"	.0025" - .0043"	.0030" - .0055"	.0035" - .0065"	.0042" - .0080"	.0052" - .0095"
M	STAINLESS STEELS								
	Free Machining (303)	300 - 400	.0020" - .0042"	.0027" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"
	Austenitic (304 / 304L)	225 - 350	.0017" - .0035"	.0025" - .0043"	.0030" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"
Martensitic (17-4 / 416)	200 - 250	.0015" - .0028"	.0018" - .0035"	.0025" - .0043"	.0030" - .0055"	.0035" - .0065"	.0042" - .0080"	.0052" - .0095"	
P	MEDIUM ALLOY TOOL STEELS								
	8620	250 - 400	.0017" - .0035"	.0025" - .0043"	.0030" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"
	4140, D2, S7	250 - 350	.0015" - .0028"	.0018" - .0035"	.0025" - .0043"	.0030" - .0055"	.0035" - .0065"	.0042" - .0080"	.0052" - .0095"
	CARBON STEELS								
	1000 Series, A36, 12L14	300 - 500	.0020" - .0042"	.0027" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"
	CAST STEELS								
Steel	250 - 350	.0020" - .0042"	.0027" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"	
K	CAST MATERIAL								
	Ductile Iron	250 - 350	.0020" - .0042"	.0027" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"
	Gray Iron	250 - 350	.0020" - .0042"	.0027" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"
N	NON-FERROUS								
	Aluminum (6061-T6)	300 - 500	.0020" - .0042"	.0027" - .0052"	.0035" - .0065"	.0043" - .0078"	.0052" - .0095"	.0065" - .0115"	.0080" - .0143"
	Copper, Brass	175 - 350	.0017" - .0042"	.0025" - .0052"	.0030" - .0065"	.0035" - .0078"	.0043" - .0095"	.0052" - .0115"	.0065" - .0143"




ap = full flute length

ae = 2%


NOTE - ABOVE ARE STARTING PARAMETERS ONLY. HIGHER RESULTS MAY BE ACHIEVED WITH OPTIMUM CONDITIONS.

Chip Thinning Calculations for TMS / TMR End Mills


ae = 3%



ae = 2%



ae = 1%



3% Radial Engagement (.03 x d)	
Actual (CPT)	Programmed (CPT)
.0002"	.0005"
.0003"	.0010"
.0005"	.0015"
.0007"	.0020"
.0009"	.0025"
.0010"	.0030"
.0012"	.0035"
.0014"	.0040"
.0015"	.0045"
.0017"	.0050"
.0019"	.0055"
.0020"	.0060"
.0022"	.0065"
.0024"	.0070"
.0026"	.0075"
.0027"	.0080"
.0029"	.0085"
.0031"	.0090"
.0032"	.0095"
.0034"	.0100"
.0036"	.0105"
.0037"	.0110"
.0039"	.0115"
.0041"	.0120"
.0043"	.0125"
.0044"	.0130"
.0046"	.0135"
.0048"	.0140"
.0049"	.0145"
.0051"	.0150"
.0053"	.0155"
.0054"	.0160"
.0056"	.0165"
.0058"	.0170"
.0060"	.0175"
.0061"	.0180"
.0063"	.0185"
.0065"	.0190"
.0066"	.0195"
.0068"	.0200"

2% Radial Engagement (.02 x d)	
Actual (CPT)	Programmed (CPT)
.0001"	.0005"
.0003"	.0010"
.0004"	.0015"
.0006"	.0020"
.0007"	.0025"
.0008"	.0030"
.0010"	.0035"
.0011"	.0040"
.0013"	.0045"
.0014"	.0050"
.0015"	.0055"
.0017"	.0060"
.0018"	.0065"
.0020"	.0070"
.0021"	.0075"
.0022"	.0080"
.0024"	.0085"
.0025"	.0090"
.0027"	.0095"
.0028"	.0100"
.0029"	.0105"
.0031"	.0110"
.0032"	.0115"
.0034"	.0120"
.0035"	.0125"
.0036"	.0130"
.0038"	.0135"
.0039"	.0140"
.0041"	.0145"
.0042"	.0150"
.0043"	.0155"
.0045"	.0160"
.0046"	.0165"
.0048"	.0170"
.0049"	.0175"
.0050"	.0180"
.0052"	.0185"
.0053"	.0190"
.0055"	.0195"
.0056"	.0200"

1% Radial Engagement (.01 x d)	
Actual (CPT)	Programmed (CPT)
.0001"	.0005"
.0002"	.0010"
.0003"	.0015"
.0004"	.0020"
.0005"	.0025"
.0006"	.0030"
.0007"	.0035"
.0008"	.0040"
.0009"	.0045"
.0010"	.0050"
.0011"	.0055"
.0012"	.0060"
.0013"	.0065"
.0014"	.0070"
.0015"	.0075"
.0016"	.0080"
.0017"	.0085"
.0018"	.0090"
.0019"	.0095"
.0020"	.0100"
.0021"	.0105"
.0022"	.0110"
.0023"	.0115"
.0024"	.0120"
.0025"	.0125"
.0026"	.0130"
.0027"	.0135"
.0028"	.0140"
.0029"	.0145"
.0030"	.0150"
.0031"	.0155"
.0032"	.0160"
.0033"	.0165"
.0034"	.0170"
.0035"	.0175"
.0036"	.0180"
.0037"	.0185"
.0038"	.0190"
.0039"	.0195"
.0040"	.0200"